



- ① 10" FOUND GREEN PLASTIC VALVE BOX, CARSON-BROOKS 910 OR EQUAL
- ② INSTALL BOX AT FINISH GRADE IN TUFF AREAS, 2" ABOVE GRADE IN PLANTING AREAS
- ③ QUICK COUPLER - SEE EQUIPMENT SCHEDULE (MOUNT 4 - 6" BELOW GRADE)
- ④ 1" GALVANIZED PIPE, LENGTH AS REQUIRED
- ⑤ 6" MIN. DEPTH CLEAN PEA GRAVEL
- ⑥ MAIN SUPPLY LINE
- ⑦ SUB-GRADE COMPACTED TO 90% (1+P)
- ⑧ 1" GALVANIZED DOUBLE ELBOW SWING JOINT
- ⑨ 1" GALVANIZED NIPPLE, MIN. LENGTH 24" BEFORE TRANSITION TO PVC PIPE
- ⑩ 1" BALL B11444 FORD VALVE
- ⑪ SCH. 30 NIPPLE
- ⑫ 2" SCH. 40 PVC SLEEVE NOTCHED OVER BALL VALVE
- ⑬ 906L WEATHERMATIC LOCKING VALVE CAP PERMANENTLY ATTACHED TO SLEEVE, TOP OF MARKER 4" - 5" BELOW GRADE

NOTE: INSTALL (1) QUICK COUPLING VALVE AT ALL VALVE BANKS AS SHOWN ON PLANS

QUICK COUPLING VALVE ASSEMBLY

HYDE PARK CITY

113 EAST CENTER
HYDE PARK, UTAH 84318
TEL. (435) 563-6507



**QUICK COUPLING
VALVE ASSEMBLY**

IR-04

DATE: 02-09-21