



NOTES:

1. WHEN MULTIPLE PIPES OCCUR IN ONE TRENCH, ADD REQUIRED SLEEVE SIZES TOGETHER FOR ONE SIZE.
2. WIRES SHALL BE IN SEPARATE CONDUIT AS PER CHART BELOW.
3. REFER TO SLEEVING DIAGRAM FOR SIZES OF ALL SLEEVES.
4. EXTEND ALL SLEEVING 12" MIN. BEYOND EDGE OF PAVING.

SLEEVE SIZE CHART

| PIPE SIZE | MIN. SLEEVE SIZE |
|-----------|------------------|
| 3/4" | 1 1/2" |
| 1" | 2" |
| 1 1/4" | 2 1/2" |
| 1 1/2" | 2 1/2" |
| 2" | 3" |
| 2 1/2" | 4" |
| 3" | 4" |
| 4" | 6" |
| 6" | 8" |

WIRE CONDUIT SIZES

| NUMBER OF WIRES | MIN. CONDUIT SIZE |
|-----------------|-------------------|
| 1-4 | 3/4" |
| 5-7 | 1" |
| 8-11 | 1 1/2" |
| 12-22 | 2" |
| 23-31 | 2 1/2" |
| 32-35 | 3" |

TYPICAL SLEEVING DETAIL AND SLEEVING DIAGRAM

HYDE PARK CITY

113 EAST CENTER
HYDE PARK, UTAH 84318
TEL: (435) 563-6507



TYPICAL SLEEVING
DETAIL AND
SLEEVING DIAGRAM

IR-08

DATE: 02-10-21